



The ultimate tool for demolition operations involving highly-reinforced concrete buildings or even metal structures. The CC series incorporates characteristics of shears and concrete crushers to ensure the delivery of unbeatable performances even in the toughest applications



- The combination of **powerful cylinders** and twin pin system ensure an enormous breaking and cutting force
- The **unique design of jaws** incorporates shaped shear blades, which, together with the cutting guide, providing the CC with incredible cutting power
- Interchangeable teeth and blades make maintenance operations easy and quick to keep the tool at full efficiency
- The **Speed-Valve** reduces opening and closing time boosting productivity
- The continuous **hydraulic rotation** enables precise positioning during high reach demolitions and the double-row thrust bearing ensures high robustness and increases safety



MODEL		CC25R	CC35R	CC65R	CC90R
ROTATION		360° Hydraulic			
EXCAVATOR WEIGHT	t	25-30	30-40	60-70	75-95
TOOL WEIGHT *	kg	2500	3500	6650	9500
OPENING (MAX/MIN)	mm	1000/0	1100/0	1525/0	1750/0
HEIGHT	mm	1960	2270	3000	3360
HYDRAULIC WORKING PRESSURE	bar	320-350	320-350	320-350	320-350
OIL FLOW	l/min	180-220	280-300	500-600	600-700

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice. * Tool weight does include Mantovanibenne top bracket.