



# MCP-IT

## INTERCHANGEABLE TEETH

A fixed head pulverizer is the ideal tool for secondary demolition on the ground. Its interchangeable plates have become a landmark in the industry and are designed to grant high productivity and easy maintenance. Its principal job is to crush concrete in order to separate the metal reinforcing bars

### TECHNICAL DATA

MODEL		MCP600-IT	MCP800-IT
EXCAVATOR WEIGHT	t	11-18	18-27
TOOL WEIGHT *	kg	1050	2200
OPENING	mm	620	830
HEIGHT MAX.	mm	1600	2070
CRP PLATE		●	●
PP PLATE		●	●
HYDRAULIC WORKING PRESSURE	bar	280-320	280-320
OIL FLOW	l/min	100-180	180-220

We are constantly improving our products and therefore we reserve the right to change the design and technical specifications without prior notice.

- The **reinforced MCP-IT structure** is designed for durability and makes the tool extremely functional to operate on the ground. In addition, it allows the crushed material to drop through for greater efficiency

- The **2 different jaw plates**, now with two separate forged parts\* for an even faster replacement, ensure a perfect fit with the specific job: the CRP plate, with a single tooth, grants higher penetration on tough concrete while the PP plate, with double teeth, maximizes productivity



PLATE CRP



PLATE PP



\* Available for MCP800-IT, MCP910-IT

- The **speed valve** reduces opening and closing time boosting productivity

MCP910-IT	MCP1000-IT	MCP1300-IT
28-38	39-50	60-90
3100	4200	8000
1000	1150	1300
2400	2700	3250
●	●	○
●	●	●
280-320	280-320	320-350
220-280	280-320	500-600

\* Tool weight does include Mantovanibenne top bracket.

○ Not available

● Available